

 <b>FUZETEC TECHNOLOGY CO., LTD.</b>	<b>NO.</b>	<b>PQ09-101E</b>		
	<b>Product Specification and Approval Sheet</b>	<b>Version</b>	<b>6</b>	<b>Page</b>

## Radial Leaded PTC Resettable Fuse : FRH Series

### 1. Summary

- (a) **RoHS Compliant (Lead Free) Product**
- (b) **Applications : Wide variety of electronic equipment**
- (c) **Product Features : Low hold current Solid state, Radial leaded product ideal for up to 60V/250V/600V**
- (d) **Operation Current : 80mA~180mA**
- (e) **Maximum Operation Voltage : 60V**
- (f) **Maximum Interrupt Voltage : 250V/600V**
- (g) **Temperature Range : -40°C to 85°C**

### 2. Agency Recognition

UL : File No. E211981  
C-UL: File No. E211981  
TÜV: File No. R 50021651

### 3. Electrical Characteristics (23°C)

Part Number	Hold Current	Trip Current	Max. Time To Trip		Maximum Current	Max Oper. Voltage	Max Int. Voltage	Typical Power	Resistance Tolerance	
			Current	Time					R <sub>MIN</sub>	R <sub>1MAX</sub>
			I <sub>H</sub> , A	I <sub>T</sub> , A					A	Sec
FRH080-250UF	0.08	0.16	0.35	4.0	3.0	60	250	1.0	14.0	33.0
FRH080-250F	0.08	0.16	0.35	4.0	3.0	60	250	1.0	14.0	33.0
FRH110-250UF	0.11	0.22	1.00	2.0	3.0	60	250	1.0	5.0	16.0
FRH110-250F	0.11	0.22	1.00	2.0	3.0	60	250	1.0	5.0	16.0
FRH120-250UF	0.12	0.24	1.00	2.0	3.0	60	250	1.0	6.0	16.0
FRH120-250F	0.12	0.24	1.00	2.0	3.0	60	250	1.0	4.0	16.0
FRH145-250UF	0.15	0.29	1.00	2.5	3.0	60	250	1.0	3.5	12.0
FRH145-250F	0.15	0.29	1.00	2.5	3.0	60	250	1.0	3.0	12.0
FRH180-250UF	0.18	0.65	1.50	10.0	10.0	60	250	1.5	0.8	4.0
FRH180-250F	0.18	0.65	1.50	11.0	10.0	60	250	1.5	0.8	4.0
FRH150-600F	0.15	0.30	1.00	5.0	3.0	60	600	1.6	6.0	22.0
FRH160-600F	0.16	0.32	1.00	7.0	3.0	60	600	1.6	4.0	18.0

I<sub>H</sub>=Hold current-maximum current at which the device will not trip at 23°C still air.  
I<sub>T</sub>=Trip current-maximum current at which the device will always trip at 23°C still air.  
V<sub>MAX</sub>=Maximum operating voltage at which the device can withstand without damage at its rated current.  
V<sub>I-MAX</sub> = Maximum interrupt voltage device can withstand for short period of time. (Not for long term.)  
I<sub>MAX</sub>= Maximum fault current device can withstand without damage at rated voltage (V<sub>MAX</sub>).  
Pd=Typical power dissipated from device when in the tripped state in 23°C still air environment.  
R<sub>MIN</sub>=Minimum device resistance at 23°C.  
R<sub>1MAX</sub>=Maximum device resistance at 23°C 1 hour after tripping .

Physical specifications:

Lead material: FRH080-250F ~ FRH180-250F Tin plated copper,22 AWG.  
FRH150-600F ~ FRH160-600F Tin plated copper,22 AWG.

Soldering characteristics:MIL-STD-202, Method 208E.

Insulating coating:Flame retardant epoxy ,meet UL-94V-0 requirement.


**NOTE :** All FRH products are designed to assist equipment to pass ITU, UL1950 or GR1089 specification.

**CAUTION :** FRH devices are not intended for continuous use of Line Voltage such as 120 VAC ~ 600VAC and above.

**NOTE :** Specification subject to change without notice.



**4. Production Dimensions (millimeter)**




Lead Size :22AWG,  
Φ 0.65 mm Diameter

Lead Size : 22AWG,  
Φ 0.65 mm Diameter

Part Number	Fig	A	B	C	D	E
		Maximum	Maximum	Typical	Minimum	Maximum
FRH080-250UF	1	5.1	9.1	5.0	4.7	3.8
FRH080-250F	1	5.8	9.6	5.0	4.7	4.6
FRH110-250UF	1	5.9	9.4	5.0	4.7	3.8
FRH110-250F	1	6.8	9.9	5.0	4.7	4.6
FRH120-250UF	2	6.0	10.0	5.0	4.7	3.8
FRH120-250F	2	6.5	11.0	5.0	4.7	4.6
FRH145-250UF	2	6.0	10.0	5.0	4.7	3.8
FRH145-250F	2	6.5	11.0	5.0	4.7	4.6
FRH180-250UF	2	10.4	12.6	5.0	4.7	3.8
FRH180-250F	2	10.9	12.6	5.0	4.7	4.6
FRH150-600F	2	14.0	12.6	5.0	4.7	6.0
FRH160-600F	2	16.0	12.6	5.0	4.7	6.0

**5. Thermal Derating Curve**




A= FRH180-250UF  
FRH180-250F  
B= All other FRH devices

**NOTE : Specification subject to change without notice.**



### 6. Typical Time-To-Trip at 23°C

- A=FRH080-250UF & FRH080-250F
- B=FRH110-250UF & FRH110-250F
- C=FRH120-250UF & FRH120-250F
- D=FRH145-250UF & FRH145-250F
- E=FRH180-250UF & FRH180-250F
- F=FRH150-600F
- G=FRH160-600F




### 7. Material Specification

- Lead material : Tin plated copper, 22 AWG.
- Soldering characteristics:MIL-STD-202, Method 208E.
- Insulating coating:Flame retardant epoxy, meets UL-94V-0 requirement

### 8. Part Numbering and Marking System


#### Part Numbering System

FRH □ □ □ - □ □ □ UF



Example

#### Part Marking System



- \* FRH150-600F Marking : RH6150F
- \* FRH160-600F Marking : RH6160F

**Warning:** -Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.



- PPTC device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
- Avoid contact of PPTC device with chemical solvent. Prolonged contact will damage the device performance.

**NOTE :** Specification subject to change without notice.