


LTE-FDD/HSPA MODULE



SIM7500A-H



The SIM7500A-H is Multi-Band LTE-FDD/HSPA module solution in a LGA type which supports LTE CAT4 up to 150Mbps for downlink data transfer.

It has strong extension capability with rich interfaces including UART, USB2.0, I2C, GPIO etc. With abundant application capability like TCP/UDP/FTP/FTPS/HTTP/HTTPS/SMTP/POP3 and MMS, the module provides much flexibility and ease of integration for customer's application.

Smart Machine Smart Decision

General features

- Tri-Band FDD-LTE B2/B4/B12
- Dual-Band UMTS/HSDPA/HSPA+ B2/B5
- Control Via AT Commands
- Supply voltage range: 3.4V~ 4.2V
- Operation temperature: -40℃ to +85℃
- Dimension: 24*27*2.75mm
- Weight: 4.0g

Specifications for Data transfer

- LTE CAT4
 - Uplink up to 50Mbps,
 - Downlink up to 150Mbps
- HSPA+
 - Uplink up to 5.76 Mbps,
 - Downlink up to 42 Mbps
- UMTS
 - Uplink/Downlink up to 384Kbps

Other features

- USB Driver for Microsoft Windows 2000/XP/Vista/Win7/Win8
- USB Driver for Windows CE/Mobile
- USB Driver for Linux /Android
- RIL supporting for Android/Windows CE/Mobile
- Automatic installation for windows
- Linux API SDK
- Firmware update via USB
- TCP/IP/IPv4/V6 Multi-PDP,MT PDP
- FTP/FTPS/HTTP/HTTPS/SMTP/POP3/DNS/MMS
- DTMF
- MBIM to Win8
- Source code of the PC manager of the device for reference

Interfaces

- USB2.0
- UART
- SIM card
- I2C
- GPIO
- ADC
- PCM

Certifications

- ROHS (plan)
- REACH (plan)

More about SIMCom SIM7500A-H
Please contact:
Tel: 86-21-32523300
Fax: 86-21-32523020
Email: simcom@sim.com
Website: www.simcomm2m.com